



2 forward cabins, 2 AFT cabin, 2 Toilets

GENERAL SPECIFICATIONS

• L.O.A	14.40 m
• Length of hull	13.68 m
• L.W.L.	12.20 m
• Width of hull	4.25 m
• Long draught (min)	2.05 m
• Long ballast weight	2 915 kg
• Short draught (min)	1.70 m
• Short ballast weight	3 240 kg
• Air draught (max)	19.05 m
• Light displacement	10 565 kg
• Fuel tank capacity	200 l
• Freshwater capacity	530 l
• Engine power	75 HP

ARCHITECTS / DESIGNERS

- Architect Naval : Berret Racoupeau
- Architect Inside : Nauta Design

EC CERTIFICATE

- Category A - 10 persons
- Category B - 11 persons
- Category C - 14 persons

STANDARD SAIL LAYOUT AND AREA

• Mainsail	44.40 m ²
• Genoa	140 % - 49.10 m ²
• Asymmetric spi	120 m ²
• I	16.43 m
• J	5.00 m
• P	15.27 m
• E	5.30 m

STANDARD EQUIPMENT

CONSTRUCTION

- Design made following European Directive requirements and according to EC certification
- Monolithic hull design in polyester
- Monolithic structural counter moulding laminated and stuck to hull
- Deck in balsa and glass fibre sandwich covered in «diamond point» type non-slip surface
- Deck hull join screwed, stuck and banded with 1 solid wood bulwark, screwed
- Cast iron keel fixed with bolts and stainless steel veneer and stuck
- Rudder hung with glass compound stock
- White coloured hull - Hull decorated in pearl grey

DECK EQUIPMENT

RIGGING

- Standard mast 9/10 electro-polished aluminium installed on the deck, 2 level(s) of advanced cross trees
- Boom in anodised aluminium
- Standing rigging in single-strand stainless steel
- Single backstay with turnbuckle
- Rigid boom down-haul with tackle
- Genoa furling system with drum on the deck
- Mainsail sheet track
- 2 genoa sheet tracks with piston adjusted traveller cars - 2 Genoa sheet return blocks
- Rigging run back to cockpit (except boom topping lift)
- Complete running rigging: Main halyard, genoa halyard with clutch on mast and cleat, Boom topping lift with cleat on mast, Mainsail foot and sheet, 2 Genoa sheets 2 fast reefing ropes, 1 manual reef
- 10 sheet clutches
- 6 Bollards

WINCHES

- 2 Self-tailing genoa sheet winches (H50.2 STC)
- 2 Self tailing rigging winches (H40.2 STC)
- 2 winch handle(s) aluminium
- 2 Winch handle boxes

SAILS

- Furling genoa with UV protective strip
- Semi full batten written sail with slider and roller slider
- Lazy Jack and Easy bag in Perle colour

MOORING -ANCHORING

- Self-bailing chain locker - Clench bolt - Hatch cover
- Stainless steel bow fitting 2 rollers
- Vertical electrical windlass 12 V - 1000 W - Remote control
- 6 Aluminium mooring cleats - Stainless steel deck line protection

PERSONNEL GUARDS

- 1 Half-open stainless steel forward pulpit - Step
- 2 stainless steel aft pushpits
- 1 Ring lifebuoy bracket
- 1 Outboard engine bracket
- 1 Flag pole socket
- Double guardrail and stainless steel stanchions - Gangway opening to port and to starboard
- 2 Stainless steel guardrails

COCKPIT

- Cockpit bottom self bailing
- 1 Port cockpit locker
- 2 Lockers under tiller seating
- 1 Gas locker for 2 bottles in cockpit bottom
- Cockpit benches decked in natural solid wood
- 2 Steering wheel consoles: Stainless steel steering wheels - 900 mm diameter - leather covered - rudder systems on partition - metal cable transmission system - Stainless steel guard rail - navigation instrument stand (optional instruments)
- 1 Deck hole for access to tiller system
- 1 Emergency tiller
- 2 Steering compass on binacle
- Engine control and control panel to starboard
- Polyester cockpit table - 2 flaps - glove boxes - central bottle holder - bottle holder on reverse side - Stainless steel guard rail - 12 V socket - lamp with shade
- 2 Waterproof loudspeakers
- 2 Companionway door on solid wood hinges - Sliding hatch made of PMMA

SUN DECK AND UPPER STERN

- Access door pivoted on pantograph (Patented)
- Natural solid wood decking on sun deck
- 1 Cased life-raft locker in upper stern - 2 doors
- 1 Stainless steel swimming ladder - solid wood steps
- 1 Shower spray hot water / cold water
- 1 Shore power socket

FITTINGS

- Alpi woodwork in fruit tree colour
- Parquet type laminated floors
- Saloon hull and bulkhead covered with vinyl fabric ceiling

COMPANIONWAY

- Height to deck beam: 1.98 m
- Wooden companionway with hung steps in moulded wood with non-slip surface
- 4 Stainless steel guardrails

FORWARD GALLERY

- 1 Double cupboard
- 1 Opening deck hatch with shutter / Mosquito net

FORWARD CABIN

- Height to deck beam: 1.95 m
- Central bed (2.20 m x 1.15 m), Marine mattress
- Hanging locker - Glove box - Cubbyholes along the hull
- 1 Hull porthole with curtain
- 1 Opening deck hatch with shutter / Mosquito net

STARBOARD FORWARD CABIN

- 2 Single bunk-bed(s) - Marine mattress (Bottom bunk (1.80 m x 0.60 m) - Top bunk (2.10 m x 0.57 m))
- Storage locker
- 1 Hull porthole with curtain
- 1 Opening deck hatch with shutter / Mosquito net

GALLEY TO PORT

- Height to deck beam: 1.94 m
- Kitchen along the hull
- White laminated worktop
- 1 Stainless steel sink 2 rectangular basins in stainless steel - 1 Mixer tap with hot/cold water under pressure
- 1 Gas cooker 2 hobs - stainless steel oven, on mountings - 1 safety bar
- 1 Ice box 170 litre top opening - Refrigeration unit 12 V
- Fitted cupboards and closed cubbyholes: Shelf Rubbish bin - tea towel holder
- 1 cutlery drawer
- 1 Hull porthole with curtain
- 1 Fitted deckhouse side window with curtain

STARBOARD SALOON

- Height to deck beam: 1.94 m
- L-shaped saloon bench seat - double density foam
- 1 Seating / Removable locker
- Central bench seat with storage locker - on pantograph
- 4 Matching decorative cushions
- Saloon table in only 1 piece - Varnished wooden top - veneering - Aluminium legs
- Cubby hole lockers - Storage space along the hull - Storage under bench seats
- 2 Panoramic deck house windows with concertina blinds
- 1 Hull porthole with curtain
- 1 Fitted deckhouse side window with curtain
- 1 Porthole opening onto coaming in side window
- 2 Opening deck hatch(es) with blind / Mosquito net

CHART TABLE TO STARBOARD

- Table with drop fronts - glove boxes - Moulded wood beading
- Pivoting electrical panel enabling access to electrical connections
- Navigation instrument panel (without instruments)
- 1 White light fitting / Red

STARBOARD AFT WASHROOM

- Access through saloon and the starboard aft cabin
- Height to deck beam: 2.05 m
- Washroom moulded in one piece to be watertight
- Separate shower, shower mixer tap hot / cold water - 2 door shower cabinet in PMMA
- Manual marine toilet
- 1 Rigid sewage water tank 80L
- Washbasin - Synthetic resin worktop, Mixing tap hot water / cold water
- Mirror
- Toilet accessories: Glass holder, soap tray, towel rail, Rubbish bin, Paper dispenser
- Cupboard and cubbyholes
- 1 Fitted deckhouse side window with curtain
- 1 Porthole(s) opening onto coaming with curtain

PORT WASHROOM AFT

- Access through saloon
- Height to deck beam: 1.95 m
- Washroom moulded in one piece to be watertight
- 1 Manual marine toilet
- Washbasin - Laminated worktop - Valve / shower mixer tap hot / cold water
- Mirror
- Toilet accessories: Glass holder - towel rail - Rubbish bin - Paper dispenser
- Cupboard and closed cubbyholes
- 1 Fitted deckhouse side window with curtain
- 1 Porthole(s) opening onto coaming with curtain

AFT CABINS

- 2 Cabins each with:
- Height to deck beam: 2.05 m
- Double bed(2 m x 1.50 m), Marine mattress
- Hanging locker, Storage space along the hull
- 1 Hull portholes with curtain
- 1 Porthole(s) opening onto coaming with curtain
- 1 Porthole(s) opening onto cockpit with curtain
- 1 Opening deck hatch with shutter / mosquito nets
- Access door to aft washroom in starboard cabin

ENGINE

- Engine Yanmar Diesel 75 hp
- Engine control - Control panel in cockpit
- Engine compartment: Foam soundproofing - Ventilation: 1 air intake and 1 pressured air outlet
- 1 Alternator 12 V / 80 Ah
- 1 Rotation moulded diesel tank 200 L (under starboard aft berth) - Electronic gauge - Low level alarm - 1 Deck filler
- Filters: Sea water - Diesel - Decanter
- Stainless steel shaft line - Polyester guard moulded into hull
- Fixed three blade propeller
- Engine access through companionway (opening with gas piston) - the passageway port, the rear cabin

ELECTRICITY

- 12 V circuit - 220 V circuit
- 2 service batteries (2x140 Ah) - 1 Battery for engine (110 Ah)
- 1 Battery charger 40 Ah - 1 Shore power socket 220V - 1 Charge divider
- Electrical panel (12 V / 220 V) (Circuit breakers - Voltmeter - Water gauge - Fuel gauge - Battery warning - Fuel warning)
- 1 Socket(s)12 V - 7 Socket(s)220 V
- Lighting: Halogen ceiling lights, Reading lights, White/red light fitting
- Navigation lights: 1 Forward and aft navigation lights - 1 Engine navigation light / Crosstree light forward of mast - 1 Mooring light on masthead - 1 Deck light
- Wire runs for options cables

PLUMBING

- 2 rotation moulded freshwater tanks (200 L port aft cabin - 330 L forward cabin) - 2 Deck fillers - Separate tank filling - Tank selection with ¼ by-pass valves
- Pressurised electric water pump - Expansion chamber - System protection filter
- Electric water heater 40 L (Operation off engine or on 220 V electrical system)
- 1 Rigid sewage water tank 80L
- Delayed shower draining and electric shower drain pumps
- 2 Electric bilge pumps - 1 Manual bilge pump
- 1 Electric ice box drain pump

GAS

- 2 Gas bottle box(es) in the cockpit
- Pressure reducing valve and safety tap

TRIM LEVEL

	AVANTAGE	ELEGANCE
2 Notches colors TFT ST70 RAYMARINE (Loch - Speedometer - Depth sounder - Weather vane - Anmomtre)	■	■
Cockpit bottom decked in natural solid wood	■	■
3 Opening portholes in fixed side windows	■	■
1 Additional opening cockpit porthole in starboard aft cabin	■	■
Freshwater foot pump - Sea water	■	■
LED indirect lighting in saloon	■	■
Navigation lights LED - Interior lights LED (Overhead lights)	■	■
2 Additional service batteries 140 amperes	■	■
1 Additional battery charger(s) 40 amperes	■	■
Releasable fore-stay chain-plate		■
1 Port electric rigging winch H40.2STCEH		■
Polyester/wood cockpit table + White PVC protective cover		■
Sheathing leather handrails on descent		■
Mirror on forward partition of fore cabin		■
Mirror at entrance door of forward cabin		■
3 hob oven/grill cooker on de luxe mounting		■

OPTIONS

PACKS

PACK ELECTRONIC RAYMARINE

- PC interface
- Swivel base on reverse side of table
- 1 Multifunction screen C90W colour 9" (GPS - tracker - Cartography Navionics Silver Europe included - Chart tracker - supplied without chart)
- Pilot SPX ST70 LS RV2 - Integrated gyrocompass - Control console
- Graphic multifunction repeater(s) ST 70

PACK EASY DOCKING

- Bow thruster
- 2 White PVC steering wheel covers
- Windlass control in cockpit with chain counter
- Complete mooring kit: (Anchor Delta 20 kg, 32 M of 10 mm chain, 48 M of 18 mm rope) - 4 Mooring ropes - 6 Fenders

OTHER OPTIONS

- 2 nd Multifunction screen C90W colour 9" at the chart table
- Remote pilot control, Wireless instruments repeater SmartController RAYMARINE
- Radar (radome only) RAYMARINE
- AIS information RAYMARINE
- VHF RAYMARINE 49 E

- Steel blue colour hull - Hull decorated in pearl grey
- Electro-polished mast furling system with sail
- Wind indicator Windex
- 2 flag halyards
- Asymmetric spinnaker rigging
- Asymmetric spinnaker rigging and boom
- Easy Sail (Genoa traveller adjustment from cockpit - Clutches on genoa sheet foot blocks - Backstay adjustment(s) - Winch handle Harken Speedgrip - Winch handle box - Emergency rope cutter)
- 3 retractable blades propeller
- Solid wood decked catwalks
- Perle deck house hood
- Cockpit Bimini top Perle
- PVC cockpit cushions

- Double berth in saloon
- Swivel foldaway saloon table
- Crockery kit marked Bénéteau
- Slat mattresses
- Porthole mosquito nets
- Heating
- Air conditioning
- Generator 5.5 KVA
- Microwave oven
- Television LCD 20"
- Player DVD - CD - MP3
- TV aerial
- Additional rigid sewage tank
- Electric toilet
- Fridge 110 litres, Refrigeration unit 12 V, front opening